

## **SharkBite**<sup>TM</sup>

## **Brass Female Sweat Adapter**

SharkBite™ expansion fittings are designed for use with PEX-a tubing and must be used in conjunction with SharkBite expansion rings. SharkBite expansion fittings have a 25-year system warranty when used with SharkBite PEX-a tubing.

## **Approved Applications**

Residential and commercial potable water, recirculation, reclaimed water systems, hydronic heating/cooling (up to 50% glycol concentration) and direct burial.



Materials	
Body	Lead-Free DZR Brass


Performance			
Max Working Pressure			
80 psi	at	200°F	
100 psi	at	180°F	
160 psi	at	73.4°F	

Minimum Length of Pipe Connecting Two Fittings			
Fittings/Pipe Size	Min. Length	Insertion Depth	
1/2 in.	2 in.	0.72 in.	
3/4 in.	2-1/2 in.	0.97 in.	
1 in.	3 in.	1.19 in.	
1-1/4 in.	4-1/2 in.	1.46 in.	
1-1/2 in.	4-1/2 in.	1.72 in.	
2 in.	6 in.	2.17 in.	

## **Certifications & Listings**

ASTM F1960, ASTM F877, CSA B137.5, NSF/ANSI 14, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, ASTM E84, CAN/ULC S102.2, ASTM E119, CAN/ULC S101

For listing information, please contact Customer Service.



Dimensions (inches)			
Part #	Size	A	В
UAB600	1/2" x 1/2" SWT	1.28	0.75
UAB605	1" x 1" SWT	2.19	1.30
UAB606	3/4" x 3/4" SWT	1.80	1.02
UAB681	1/2" x 3/4" SWT	1.56	1.02
UAB683	3/4" x 1/2" SWT	1.52	0.75
UAB685	3/4" x 1" SWT	1.95	1.30
UAB143535F	1-1/4" x 1-1/4" SWT	2.52	1.85
UAB144141F	1-1/2" x 1-1/2" SWT	2.95	2.20
UAB145454F	2" x 2" SWT	3.70	2.68

Product Submittal		
Name		
Date		
Architect/Owner		
Contractor		
Tag		
Notes		

Rev 2.0 / 07-17-23 Page 1 of 1 EN-US

