

# SharkBite<sup>TM</sup> Brass Swivel Adapter

SharkBite<sup>™</sup> expansion fittings are designed for use with PEX-a tubing and must be used in conjunction with SharkBite expansion rings. SharkBite expansion fittings have a 25-year system warranty when used with SharkBite PEX-a tubing.

## **Approved Applications**

Residential and commercial potable water, recirculation, reclaimed water systems, hydronic heating/cooling (up to 50% glycol concentration) and direct burial.

## **Specification Data**


Materials					
Body		Lead-Free DZR Brass			
Performance					
Max Working Press	ure				
80 psi	at	200°F			
100 psi	at	180°F			
160 psi	at	73.4°F			

Minimum Length of Pipe Connecting Two Fittings				
Fittings/Pipe Size	Min. Length	Insertion Depth		
1/2 in.	2 in.	0.72 in.		
3/4 in.	2-1/2 in.	0.97 in.		
1 in.	3 in.	1.19 in.		
1-1/4 in.	4-1/2 in.	1.46 in.		
1-1/2 in.	4-1/2 in.	1.72 in.		
2 in.	6 in.	2.17 in.		

### **Certifications & Listings**

ASTM F1960, ASTM F877, CSA B137.5, NSF/ANSI 14, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372

For listing information, please contact Customer Service.



#### Dimensions (inches)

Part #	Size	Α	В
UAB526	1/2" x 1/2" NPSM	1.29	1.07
UAB530	3/4" x 3/4" NPSM	1.68	1.33

Product Submittal				
Name				
Date				
Architect/Owner				
Contractor				
Tag				
Notes				

US 18777004242 | sales@sharkbite.com | sharkbite.com Canada 18888200120 | canadasales@rwc.com Rev 2.0 / 07-17-23 Page 1 of 1 EN-US



This information is proprietary to RWC and is subject to change without notice. It may not be reproduced in part or whole without written authorization.