

# **SharkBite**<sup>TM</sup>

## **Poly Plug**

SharkBite™ expansion fittings are designed for use with PEX-a tubing and must be used in conjunction with SharkBite expansion rings. SharkBite expansion fittings have a 25-year system warranty when used with SharkBite PEX-a tubing.

#### **Approved Applications**

Residential and commercial potable water, recirculation, reclaimed water systems, hydronic heating/cooling (up to 50% glycol concentration) and direct burial.

### **Specification Data**

Materials	
Body	PPSU


Performance			
Max Working Pressure			
80 psi	at	200°F	
100 psi	at	180°F	
160 psi	at	73.4°F	

Minimum Length of Pipe Connecting Two Fittings				
Fittings/Pipe Size	Min. Length	Insertion Depth		
1/2 in.	2 in.	0.72 in.		
3/4 in.	2-1/2 in.	0.97 in.		
1 in.	3 in.	1.19 in.		
1-1/4 in.	4-1/2 in.	1.46 in.		
1-1/2 in.	4-1/2 in.	1.72 in.		
2 in.	6 in.	2.17 in.		

#### **Certifications & Listings**

ASTM F1960, ASTM F877, CSA B137.5, NSF/ANSI 14, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, ASTM E84, CAN/ULC S102.2, ASTM E119, CAN/ULC S101

For listing information, please contact Customer Service.



Dimensions (inches)			
Part #	Size	A	В
UA514	1/2"	0.83	0.85
UA518	3/4"	1.07	1.13
UA520	1"	1.31	1.42
UA0435	1-1/4"	1.63	1.70
UA0441	1-1/2"	1.90	1.81
UA0454	2"	2.38	2.51

Product Submittal	
Name	
Date	
Architect/Owner	
Contractor	
Tag	
Notes	

Rev 3.0 / 07-17-23 Page 1 of 1 EN-US

